

Lampiran 1 : Tabel Pengambilan & Pengolahan Data

Larutan	Volume Alir Gas (Q), Tegangan (V), Temperatur (C)											
	2A			4A			6A			8A		
	Q (l/s)	V (Volt)	T (C)	Q (l/s)	V (Volt)	T (C)	Q (l/s)	V (Volt)	T (C)	Q (l/s)	V (Volt)	T (C)
Aquades Murni	0.00026	15.52	28	0.0005	24.36	31.66	0.00076	32.36	37	0.00124	44.16	45
0.99%	0.0002	2.74	27	0.00047	3.04	27.5	0.00076	3.27	28	0.00098	3.44	28
1.15%	0.00027	2.79	27	0.00062	3.12	27	0.00095	3.35	27.66	0.00131	3.56	28
1.31%	0.00033	2.73	27	0.00069	3.08	27.83	0.00123	3.32	28	0.00171	3.51	28.66
1.48%	0.00026	3.07	27	0.0006	3.07	28	0.00109	3.3	28	0.00167	3.5	28
1.64%	0.00014	2.81	27	0.0004	3.15	27	0.00075	3.37	28	0.00117	3.62	28
AMDK Murni	0.00043	3.98	28.66	0.00078	5.12	29.33	0.00112	6.25	30.5	0.00145	7.41	32.166

Larutan	Hambatan ( $\Omega$ ), Daya (Watt), Efisiensi ( $\eta$ )											
	2A			4A			6A			8A		
	$\Omega$ (Ohm)	P (Watt)	$\eta$ (%)	$\Omega$ (Ohm)	P (Watt)	$\eta$ (%)	$\Omega$ (Ohm)	P (Watt)	$\eta$ (%)	$\Omega$ (Ohm)	P (Watt)	$\eta$ (%)
Aquades Murni	7.76	31.04	5.53	6.09	97.46	3.34	5.39	194.19	2.53	5.52	353.32	2.28
0.99%	1.37	5.48	24.04	0.76	12.17	25.08	0.54	19.66	25.27	0.43	27.59	22.99
1.15%	1.39	5.58	31.06	0.78	12.48	32.3	0.55	20.11	30.64	0.44	28.49	30
1.31%	1.36	5.47	38.96	0.77	12.33	36.5	0.55	19.94	40.13	0.43	28.13	39.51
1.48%	1.53	6.15	27.61	0.76	12.28	31.78	0.55	19.82	35.77	0.43	28	38.73
1.64%	1.4	5.63	16.34	0.78	12.61	20.49	0.56	20.25	24.19	0.45	29	26.25
AMDK Murni	1.99	7.97	34.67	1.28	20.48	24.88	1.04	37.54	19.45	0.92	59.32	15.94